

C.Rudduck Pty Ltd

Version No: 1.1

Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

Chemwatch Hazard Alert Code: 4

lssue Date: 04/04/2023 Print Date: 04/04/2023 S.GHS.AUS.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

| Product Identifier | |
|-------------------------------|----------------------|
| Product name | Py Insecticide Spray |
| Synonyms | Not Available |
| Proper shipping name | AEROSOLS |
| Other means of identification | Not Available |

Relevant identified uses of the substance or mixture and uses advised against

| Relevant identified uses | Aerosol Insecticide |
|--------------------------|---------------------|

Details of the manufacturer or supplier of the safety data sheet

| Registered company name | C.Rudduck Pty Ltd |
|-------------------------|---|
| Address | 2/247 Ingles Street, Port Melbourne Victoria 3207 Australia |
| Telephone | 03 9676 4444 |
| Fax | Not Available |
| Website | Not Available |
| Email | Not Available |

Emergency telephone number

| Association / Organisation | C.Rudduck Pty Ltd | CHEMWATCH EMERGENCY RESPONSE (24/7) |
|-----------------------------------|-------------------|-------------------------------------|
| Emergency telephone numbers | 0418 355 009 | +61 1800 951 288 |
| Other emergency telephone numbers | Not Available | +61 3 9573 3188 |

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

| Poisons Schedule | Not Applicable |
|-------------------------------|--|
| Classification ^[1] | Hazardous to the Aquatic Environment Long-Term Hazard Category 2, Aspiration Hazard Category 1, Hazardous to the Aquatic Environment Acute Hazard Category 2, Aerosols Category 1 |
| Legend: | 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI |

Label elements

| Hazard pictogram(s) | | | × |
|---------------------|--|--|---|
|---------------------|--|--|---|

Signal word Dang

Danger

Hazard statement(s)

| H411 | Toxic to aquatic life with long lasting effects. |
|-----------|--|
| AUH044 | Risk of explosion if heated under confinement. |
| H304 | May be fatal if swallowed and enters airways. |
| H222+H229 | Extremely flammable aerosol. Pressurized container: may burst if heated. |

Precautionary statement(s) Prevention

| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
|------|--|
| P211 | Do not spray on an open flame or other ignition source. |
| P251 | Do not pierce or burn, even after use. |
| P273 | Avoid release to the environment. |
| | |

Precautionary statement(s) Response

| P301+P310 | IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider. | |
|-----------|--|--|
| P331 | Do NOT induce vomiting. | |
| P391 | Collect spillage. | |
| | | |

Precautionary statement(s) Storage

| P405 | Store locked up. |
|-----------|--|
| P410+P412 | Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. |

Precautionary statement(s) Disposal

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

P501

Substances

See section below for composition of Mixtures

Mixtures

| Mixtures | | |
|-------------|---|--------------------|
| CAS No | %[weight] | Name |
| 68475-59-2. | >60 | alkanes C3-4. |
| 93924-07-3 | 30-60 | C10-14 alkanes |
| 51-03-6 | <5 | piperonyl butoxide |
| 121-21-1 | <1 | pyrethrin I |
| Legend: | 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L: * EU IOELVs available | |

SECTION 4 First aid measures

| Description of first aid measures | | |
|-----------------------------------|---|--|
| Eye Contact | If aerosols come in contact with the eyes: Immediately hold the eyelids apart and flush the eye with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. | |
| Skin Contact | If solids or aerosol mists are deposited upon the skin: Flush skin and hair with running water (and soap if available). Remove any adhering solids with industrial skin cleansing cream. DO NOT use solvents. Seek medical attention in the event of irritation. | |
| Inhalation | If aerosols, fumes or combustion products are inhaled: Remove to fresh air. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor. | |
| Ingestion | If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice. Avoid giving milk or oils. Avoid giving alcohol. If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus. | |

Indication of any immediate medical attention and special treatment needed

For petroleum distillates

In case of ingestion, gastric lavage with activated charcoal can be used promptly to prevent absorption - decontamination (induced emesis or lavage) is controversial and should be considered on the merits of each individual case; of course the usual precautions of an endotracheal tube should be considered prior to lavage, to prevent aspiration.
 Individuals intoxicated by petroleum distillates should be hospitalized immediately, with acute and continuing attention to neurologic and cardiopulmonary function.

- · Positive pressure ventilation may be necessary.
- · Acute central nervous system signs and symptoms may result from large ingestions of aspiration-induced hypoxia.

• After the initial episode, individuals should be followed for changes in blood variables and the delayed appearance of pulmonary oedema and chemical pneumonitis. Such patients should be followed for several days or weeks for delayed effects, including bone marrow toxicity, hepatic and renal impairment Individuals with chronic pulmonary disease will be more seriously impaired, and recovery from inhalation exposure may be complicated.

Gastrointestinal symptoms are usually minor and pathological changes of the liver and kidneys are reported to be uncommon in acute intoxications.

• Chlorinated and non-chlorinated hydrocarbons may sensitize the heart to epinephrine and other circulating catecholamines so that arrhythmias may occur. Careful consideration of this potential adverse effect should precede administration of epinephrine or other cardiac stimulants and the selection of bronchodilators.

Treat symptomatically.

For chronic or short term repeated exposures to pyrethrum and synthetic pyrethroids:

- Mammalian toxicity of pyrethrum and synthetic pyrethroids is low, in part because of poor bioavailability and a large first pass extraction by the liver.
- The most common adverse reaction results from the potent sensitising effects of pyrethrins.
- Clinical manifestations of exposure include contact dermatitis (erythema, vesiculation, bullae); anaphylactoid reactions (pallor, tachycardia, diaphoresis) and asthma. [Ellenhorn Barceloux]
- In cases of skin contact, it has been reported that topical application of Vitamin E Acetate (alpha-tocopherol acetate) has been found to have high therapeutic value, eliminating almost all skin pain associated with exposure to synthetic pyrethroids. [Incitec]

SECTION 5 Firefighting measures

Extinguishing media

SMALL FIRE:

Water spray, dry chemical or CO2

- LARGE FIRE:
- Water spray or fog.

Special hazards arising from the substrate or mixture

| Fire Incompatibility | Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result |
|-------------------------|--|
| Advice for firefighters | |
| | |

| Fire Fighting | |
|-----------------------|--|
| Fire/Explosion Hazard | carbon dioxide (CO2) other pyrolysis products typical of burning organic material. Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions. May emit clouds of acrid smoke BEWARE: Empty solvent, paint, lacquer and flammable liquid drums present a severe explosion hazard if cut by flame torch or welded. Even when thoroughly cleaned or reconditioned the drum seams may retain sufficient solvent to generate an explosive atmosphere in the drum. WARNING: Aerosol containers may present pressure related hazards. |
| HAZCHEM | Not Applicable |

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

| Minor Spills | Environmental hazard - contain spillage. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Wear protective clothing, impervious gloves and safety glasses. Shut off all possible sources of ignition and increase ventilation. Wipe up. If safe, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely. |
|--------------|---|
| Major Spills | Environmental hazard - contain spillage. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water courses No smoking, naked lights or ignition sources. Increase ventilation. Stop leak if safe to do so. Water spray or fog may be used to disperse / absorb vapour. Absorb or cover spill with sand, earth, inert materials or vermiculite. If safe, damaged cans should be placed in a container outdoors, away from ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely. Collect residues and seal in labelled drums for disposal. |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

| Safe handling | Radon and its radioactive decay products are hazardous if inhaled or ingested The conductivity of this material may make it a static accumulator., A liquid is typically considered nonconductive if its conductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid. Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. Avoid sonking, naked lights or ignition sources. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. DO NOT incinerate or puncture aerosol cans. DO NOT incinerate or puncture aerosol cans. Avoig and water after handling. Work clothes should be laundered separately. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained. |
|-------------------|---|
| Other information | |

Conditions for safe storage, including any incompatibilities

| Suitable container | For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure. For materials with a viscosity of at least 2680 cSt. (23 deg. C) For manufactured product having a viscosity of at least 250 cSt. (23 deg. C) Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C): (i) Removable head packaging; (ii) Cans with friction closures and (iii) low pressure tubes and cartridges may be used. Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages In addition, where inner packagings are glass and contain liquids of packing group I there must be sufficient inert absorbent to absorb any spillage, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic. Aerosol dispenser. Check that containers are clearly labelled. |
|-------------------------|---|
| Storage incompatibility | Low molecular weight alkanes: May react violently with strong oxidisers, chlorine, chlorine dioxide, dioxygenyl tetrafluoroborate. May react with oxidising materials, nickel carbonyl in the presence of oxygen, heat. Are incompatible with nitronium tetrafluoroborate(1-), halogens and interhalogens may generate electrostatic charges, due to low conductivity, on flow or agitation. Avoid flame and ignition sources Redox reactions of alkanes, in particular with oxygen and the halogens, are possible as the carbon atoms are in a strongly reduced condition. Reaction with oxygen (if present in sufficient quantity to satisfy the reaction stoichiometry) leads to combustion without any smoke, producing carbon dioxide and water. Free radical halogenation reactions occur with halogens, leading to the production of haloalkanes. In addition, alkanes have been shown to interact with, and bind to, certain transition metal complexes Interaction between chlorine and ethane over activated carbon at 350 deg C has caused explosions, but added carbon dioxide reduces the risk. The violent interaction of liquid chlorine injected into ethane at 80 deg C/10 bar becomes very violent if ethylene is also present A mixture prepared at -196 deg C with either methane or ethane exploded when the temp was raised to -78 deg C. Addition of nickel carbonyl to an n-butane-oxygen mixture causes an explosion at 20-40 deg C. Alkanes will react with steam in the presence of a nickel catalyst to give hydrogen. Avoid reaction with oxidising agents |

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

| Source | Ingredient | Material name | TWA | STEL | Peak | Notes |
|------------------------------|---------------|-------------------------------|-----------------------|---------------|---------------|---------------|
| Australia Exposure Standards | alkanes C3-4. | LPG (liquified petroleum gas) | 1000 ppm / 1800 mg/m3 | Not Available | Not Available | Not Available |
| Australia Exposure Standards | alkanes C3-4. | Butane | 800 ppm / 1900 mg/m3 | Not Available | Not Available | Not Available |

Emergency Limits

| Ingredient | TEEL-1 TEEL-2 | | | TEEL-3 |
|--------------------|---------------|---------------|---------------|---------------|
| alkanes C3-4. | Not Available | Not Available | | Not Available |
| alkanes C3-4. | 65,000 ppm | 2.30E+05 ppm | | 4.00E+05 ppm |
| piperonyl butoxide | 6.5 mg/m3 | 72 mg/m3 | | 1,200 mg/m3 |
| pyrethrin I | 15 mg/m3 | 25 mg/m3 | | 150 mg/m3 |
| | | | | |
| Ingredient | Original IDLH | | Revised IDLH | |
| alkanes C3-4. | 2,000 ppm | | 1,600 ppm | |
| C10-14 alkanes | Not Available | | Not Available | |
| piperonyl butoxide | Not Available | | Not Available | |

| Ingredient | Original IDLH | Revised IDLH | | |
|--|--|--|--|--|
| pyrethrin I | Not Available Not Available | | | |
| Exposure controls | | | | |
| | Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. General exhaust is adequate under normal conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant. | | | |
| | Type of Contaminant: | | | Speed: |
| Appropriate engineering | aerosols, (released at low velocity into zone of active gene | eration) | | 0.5-1 m/s |
| controls | direct spray, spray painting in shallow booths, gas dischar | ge (active generation into zone of | rapid air motion) | 1-2.5 m/s (200-500 f/min.) |
| | Within each range the appropriate value depends on: | | | |
| | Lower end of the range | Upper end of the range |] | |
| | 1: Room air currents minimal or favourable to capture | 1: Disturbing room air currents | | |
| | 2: Contaminants of low toxicity or of nuisance value only. | 2: Contaminants of high toxicity | | |
| | 3: Intermittent, low production. | 3: High production, heavy use | | |
| | 4: Large hood or large air mass in motion | 4: Small hood-local control only | • | |
| Individual protection | 1-2 m/s (200-400 f/min.) for extraction of solvents generate considerations, producing performance deficits within the e factors of 10 or more when extraction systems are installed | d in a tank 2 meters distant from the traction apparatus, make it esser or used. | he extraction poin ntial that theoretic | t. Other mechanical al air velocities are multiplied by |
| measures, such as personal protective equipment | | | | |
| Eye and face protection | Safety glasses with side shields Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent] No special equipment for minor exposure i.e. when handling small quantities. OTHERWISE: For potentially moderate or heavy exposures: Safety glasses with side shields. Not the source of the s | | | |
| Skin protection | See Hand protection below | | | |
| Hands/feet protection | No special equipment needed when handling small quantities. OTHERWISE: For potentially moderate exposures: Wear general protective gloves, eg. light weight rubber gloves. For potentially heavy exposures: Wear chemical protective gloves, eg. PVC. and safety footwear. Insulated gloves: NOTE: Insulated gloves should be loose fitting so that may be removed quickly if liquid is spilled upon them. Insulated gloves are not made to permit hands to be placed in the liquid; they provide only short-term protection from accidental contact with the liquid. | | | |
| Body protection | See Other protection below | | | |
| Other protection | No special equipment needed when handling small quantiti OTHERWISE: • Overalls. • Skin cleansing cream. • Eyewash unit. • Do not spray on hot surfaces. | es. | | |

Respiratory protection

Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|------------------------------------|----------------------|----------------------|------------------------|
| up to 5 x ES | Air-line* | AX-2 P2 | AX-PAPR-2 P2 ^ |
| up to 10 x ES | - | AX-3 P2 | - |
| 10+ x ES | - | Air-line** | - |

* - Continuous Flow; ** - Continuous-flow or positive pressure demand

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

+ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.

The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

Generally not applicable.

Aerosols, in common with most vapours/ mists, should never be used in confined spaces without adequate ventilation. Aerosols, containing agents designed to enhance or mask smell, have triggered allergic reactions in predisposed individuals.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

| Appearance | Not Available | | |
|---|-------------------|---|---------------|
| | I | | |
| Physical state | Liquified Gas | Relative density (Water = 1) | 1 |
| Odour | Not Available | Partition coefficient n-octanol / water | Not Available |
| Odour threshold | Not Available | Auto-ignition temperature (°C) | Not Available |
| pH (as supplied) | Not Available | Decomposition temperature (°C) | Not Available |
| Melting point / freezing point (°C) | Not Available | Viscosity (cSt) | Not Available |
| Initial boiling point and boiling range (°C) | Not Available | Molecular weight (g/mol) | Not Available |
| Flash point (°C) | -18 | Taste | Not Available |
| Evaporation rate | Not Available | Explosive properties | Not Available |
| Flammability | HIGHLY FLAMMABLE. | Oxidising properties | Not Available |
| Upper Explosive Limit (%) | 7.6 | Surface Tension (dyn/cm or mN/m) | Not Available |
| Lower Explosive Limit (%) | 1.4 | Volatile Component (%vol) | Not Available |
| Vapour pressure (kPa) | Not Available | Gas group | Not Available |
| Solubility in water | Miscible | pH as a solution (1%) | Not Available |
| Vapour density (Air = 1) | Not Available | VOC g/L | Not Available |

SECTION 10 Stability and reactivity

| Reactivity | See section 7 |
|-------------------------------------|--|
| Chemical stability | Elevated temperatures. Presence of open flame. Product is considered stable. Hazardous polymerisation will not occur. |
| Possibility of hazardous reactions | See section 7 |
| Conditions to avoid | See section 7 |
| Incompatible materials | See section 7 |
| Hazardous decomposition products | See section 5 |

SECTION 11 Toxicological information

| Inhaled | The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Inhaling high concentrations of mixed hydrocarbons can cause narcosis, with nausea, vomiting and lightheadedness. Low molecular weight (C2-C12) hydrocarbons can irritate mucous membranes and cause incoordination, giddiness, nausea, vertigo, confusion, headache, appetite loss, drowsiness, tremors and stupor. Inhalation hazard is increased at higher temperatures. Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour may displace and replace air in breathing zone, acting as a simple asphyxiant. This may happen with little warning of overexposure. Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination. WWARNING:Intentional misuse by concentrating/inhaling contents may be lethal. | | |
|----------------------|--|--|--|
| Ingestion | Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733) Exposure to the piperidines may result in increased blood pressure and heart rate, nausea, vomiting, salivation, laboured breathing, muscular weakness, paralysis and convulsions. It may also excite the senses of hearing and touch. Not normally a hazard due to physical form of product. | | |
| Skin Contact | Considered an unlikely route of entry in commercial/industrial environments The material is not thought to be a skin irritant (as classified by EC Directives using animal models). Temporary discomfort, however, may result from prolonged dermal exposures. Skin contact with the material may damage the health of the individual; systemic effects may result following absorption. Spray mist may produce discomfort Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected | | |
| Eye | Although the material is not thought to be an irritant (as class characterised by tearing or conjunctival redness (as with win | ified by EC Directives), direct contact with the eye may produce transient discomfort dburn). | |
| Chronic | There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment. Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function. Skin exposure may result in drying and cracking and redness of the skin. Long-term exposure to methylenedioxyphenols (piperonyls or piperonylbutoxide) in animals causes reduced platelets (blood cells responsible for blood clotting), weight increase to the liver and thyroid, and damage to the liver, thyroid and nerves. They are reported not to cause genetic damage but affects body immune system, internal regulation, reproduction and development. Animal testing suggests that they can cause gut ulcers and bleeding from the gut, abdominal swelling, bleeding from the nose, accumulation of fluid in the lung, laboured breathing and inco-ordination. A cancer-causing effect has been noted in animal studies but this is unproven in humans. | | |
| | | | |
| Py Insecticide Spray | TOXICITY Not Available | IRRITATION Not Available | |
| alkanaa C2 4 | ΤΟΧΙΟΙΤΥ | IRRITATION | |
| aikanes C3-4. | Inhalation(Rat) LC50: 658 mg/l4h ^[2] | Not Available | |
| | ΤΟΧΙCITY | IRRITATION | |
| C10-14 alkanes | Not Available | Not Available | |
| | τοχιατχ | IBRITATION | |
| | Dermal (rabbit) D50: >2000 mg/kg ^[1] | Not Available | |
| piperonyl butoxide | Inhalation/Bat) C50: >5.2 mg/l4h ^[1] | | |
| | Oral (Rat) LD50: >2000 mg/kg ^[1] | | |
| | | | |
| pyrethrin I | Oral (Rat) LD50: 260 mg/kg ^[2] | Not Available | |
| l eaend: | 1 Value obtained from Europe ECHA Registered Substance | s - Acute toxicity 2 Value obtained from manufacturer's SDS 1 Inless otherwise | |
| | specified data extracted from RTECS - Register of Toxic Effe | ect of chemical Substances | |
| | | | |
| Py Insecticide Spray | Chronic inhalation exposures may show indications of periph | eral neuropathy, a progressive nerve disorder of extremities. | |
| ALKANES C3-4. | inhalation of the gas | | |
| PIPERONYL BUTOXIDE | Dermal (rabbit) LD50: >1880 mg/kg [Handbook of Toxicology] *Published value - probably not peer-reviewed ADI: 0.03 mg/kg The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing. | | |
| PYRETHRIN I | NOTE: Studies with rats and mice indicate rapid oxidation of (0.3%) (1). Some unmetabolised substance is found in faece substance (1). Hutson D.H; Progress in Drug Metabolism 3:2 Pyrethrins have low to moderate acute toxicity when swallow | pyrethrin I. Within 48 hrs. metabolites appear in urine (46%) and in expired CO2 s (2). The synergist, piperonyl butoxide, does not enhance the acute toxicity of the 15-252 1979 (2). Hayes W.J.; Pesticide Studies in Man William & Wilkins pp 75-80 red, inhaled and on skin contact. | |

They have a moderate irritant effect on the eye and skin (but do not sensitise the skin). The toxic effects of pyrethrin include tremors, laboured breathing, hyperactivity, thyroid disturbances, and liver effects. Animal testing has found

that pyrethrins can cause tremors and convulsions before death and that pyrethrins are toxic to the axon.

In testing involving animals, pyrethrins have been found to cause reproductive toxicity at sufficient doses, as well as benign liver tumours. There is not enough information to assess whether pyrethrins cause cancer in humans. There is evidence that pyrethrins are associated with disturbance of thyroid function. Pyrethroids are thought to have similar effects to pyrethrins. ALKANES C3-4. & C10-14 No significant acute toxicological data identified in literature search. ALKANES × Carcinogenicity × Acute Toxicity × X Skin Irritation/Corrosion Reproductivity × Serious Eye Damage/Irritation × STOT - Single Exposure Respiratory or Skin X STOT - Repeated Exposure × sensitisation Mutagenicity × Aspiration Hazard Legend: X – Data either not available or does not fill the criteria for classification

· <u>0</u>]

— Data either not available or does not fill the criteria for classification — Data available to make classification

SECTION 12 Ecological information

Toxicity

| | Endpoint | Test Duration (hr) | Species | Value | Source |
|----------------------|------------------|--------------------|-------------------------------|------------------|------------------|
| Py Insecticide Spray | Not Available | Not Available | Not Available | Not Available | Not Available |
| | Endpoint | Test Duration (hr) | Species | Value | Source |
| | LC50 | 96h | Fish | 24.11mg/l | 2 |
| alkanes C3-4. | EC50(ECx) | 96h | Algae or other aquatic plants | 7.71mg/l | 2 |
| | EC50 | 96h | Algae or other aquatic plants | 7.71mg/l | 2 |
| | Endpoint | Test Duration (hr) | Species | Value | Source |
| C10-14 alkanes | Not Available | Not Available | Not Available Not Available | | Not Available |
| | Endpoint | Test Duration (hr) | Species | Value | Source |
| | NOEC(ECx) | 48h | Crustacea | 0.01mg/l | 4 |
| piperonyl butoxide | LC50 | 96h | Fish | 1-3.3mg/l | 4 |
| | EC50 | 72h | Algae or other aquatic plants | 0.85mg/l | 2 |
| | EC50 | 48h | Crustacea | 0.46-0.674mg/L | 4 |
| pyrethrin I | Endpoint | Test Duration (hr) | Species | Species Value | |
| | Not Available | Not Available | Not Available | Not Available | Not Available |

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

- Bioconcentration Data 8. Vendor Data

Toxic to bees.

For petroleum distillates:

Environmental fate:

When petroleum substances are released into the environment, four major fate processes will take place: dissolution in water, volatilization, biodegradation and adsorption. These processes will cause changes in the composition of these UVCB substances. In the case of spills on land or water surfaces, photodegradation-another fate process-can also be

significant.

As noted previously, the solubility and vapour pressure of components within a mixture will differ from those of the component alone. These interactions are complex for complex UVCBs such as petroleum hydrocarbons.

Each of the fate processes affects hydrocarbon families differently. Aromatics tend to be more water-soluble than aliphatics of the same carbon number, whereas aliphatics tend to be more volatile. Thus, when a petroleum mixture is released into the environment, the principal water contaminants are likely to be aromatics, whereas aliphatics will be the principal air contaminants. The trend in volatility by component class is as follows: alkenes = alkanes > aromatics = cycloalkanes.

The most soluble and volatile components have the lowest molecular weight; thus there is a general shift to higher molecular weight components in residual materials.

Biodegradation:

Biodegradation is almost always operative when petroleum mixtures are released into the environment. It has been widely demonstrated that nearly all soils and sediments have populations of bacteria and other organisms capable of degrading petroleum hydrocarbons Degradation occurs both in the presence and absence of oxygen. Two key factors that determine degradation rates are oxygen supply and molecular structure. In general, degradation is more rapid under aerobic conditions. Decreasing trends in degradation rates according to structure are as follows:

(1) n-alkanes, especially in the C10-C25 range, which are degraded readily;

(2) isoalkanes;

(3) alkenes;

(4) benzene, toluene, ethylbenzene, xylenes (BTEX) (when present in concentrations that are not toxic to microorganisms);

(5) monoaromatics;

(6) polynuclear (polycyclic) aromatic hydrocarbons (PAHs); and

(7) higher molecular weight cycloalkanes (which may degrade very slowly.

Three weathering processes-dissolution in water, volatilization and biodegradation-typically result in the depletion of the more readily soluble, volatile and degradable compounds and the accumulation of those most resistant to these processes in residues.

When large quantities of a hydrocarbon mixture enter the soil compartment, soil organic matter and other sorption sites in soil are fully saturated and the hydrocarbons will begin to form a separate phase (a non-aqueous phase liquid, or NAPL) in the soil. At concentrations below the retention capacity for the hydrocarbon in the soil, the NAPL will be immobile this is referred to as residual NAPL. Above the retention capacity, the NAPL becomes mobile and will move within the soil

Bioaccumulation: Bioaccumulation potential was characterized based on empirical and/or modelled data for a suite of petroleum hydrocarbons expected to occur in petroleum substances. Bioaccumulation factors (BAFs) are the preferred metric for assessing the bioaccumulation potential of substances, as the bioconcentration factor (BCF) may not adequately account

for the bioaccumulation potential of substances via the diet, which predominates for substances with log Kow > ~4.5 In addition to fish BCF and BAF data, bioaccumulation data for aquatic invertebrate species were also considered. Biota-sediment/soil accumulation factors (BSAFs), trophic magnification factors and biomagnification factors were also considered in characterizing bioaccumulation potential.

Overall, there is consistent empirical and predicted evidence to suggest that the following components have the potential for high bioaccumulation, with BAF/BCF values greater than 5000: C13–C15 isoalkanes, C12 alkenes, C12–C15 one-ring cycloalkanes, C12 and C15 two-ring cycloalkanes, C14 polycycloalkanes, C15 one-ring aromatics, C15 and C20 cycloalkane monoaromatics. C12–C13 diaromatics. C20 cycloalkane diaromatics, and C14 and C20 three-ring PAHs

These components are associated with a slow rate of metabolism and are highly lipophilic. Exposures from water and diet, when combined, suggest that the rate of uptake would exceed that of the total elimination rate. Most of these components are not expected to biomagnify in aquatic or terrestrial foodwebs, largely because a combination of metabolism, low dietary assimilation efficiency and growth dilution allows the elimination rate to exceed the uptake rate from the diet; however,

one study suggests that some alkyl-PAHs may biomagnify. While only BSAFs were found for some PAHs, it is possible that BSAFs will be > 1 for invertebrates, given that they do not have the same metabolic competency as fish.

In general, fish can efficiently metabolize aromatic compounds. There is some evidence that alkylation increases bioaccumulation of naphthalene but it is not known if this can be generalized to larger PAHs or if any potential increase in bioaccumulation due to alkylation will be sufficient to exceed a BAF/BCF of 5000.

Some lower trophic level organisms (i.e., invertebrates) appear to lack the capacity to efficiently metabolize aromatic compounds, resulting in high bioaccumulation potential for some aromatic components as compared to fish.

This is the case for the C14 three-ring PAH, which was bioconcentrated to a high level (BCF > 5000) by invertebrates but not by fish. There is potential for such bioaccumulative components to reach toxic levels in organisms if exposure is continuous and of sufficient magnitude, though this is unlikely in the water column following a spill scenario due to relatively rapid dispersal

Bioaccumulation of aromatic compounds might be lower in natural environments than what is observed in the laboratory. PAHs may sorb to organic material suspended in the water column (dissolved humic material), which decreases their overall bioavailability primarily due to an increase in size. This has been observed with fish Ecotoxicity:

Diesel fuel studies in salt water are available. The values varied greatly for aquatic species such as rainbow trout and Daphnia magna, demonstrating the inherent variability of diesel fuel compositions and its effects on toxicity. Most experimental acute toxicity values are above 1 mg/L. The lowest 48-hour LC50 for salmonids was 2.4 mg/L. Daphnia magna had a 24-hour LC50 of 1.8 mg/. The values varied greatly for aquatic species such as rainbow trout and Daphnia magna, demonstrating the inherent variability of diesel fuel compositions and its effects on toxicity. Most experimental acute toxicity values are above 1 mg/L. The lowest 48-hour LC50 for salmonids was 2.4 mg/L. Daphnia magna had a 24-hour LC50 of 1.8 mg/. Most experimental acute toxicity values are above 1 mg/L. The lowest 48-hour LC50 for salmonids was 2.4 mg/L. Daphnia magna had a 24-hour LC50 of 1.8 mg/L. Daphnia magna had a 24-hour LC50 of 1.8 mg/L.

The tropical mysid Metamysidopsis insularis was shown to be very sensitive to diesel fuel, with a 96-hour LC50 value of 0.22 mg/L this species has been shown to be as sensitive as temperate mysids to toxicants. However, However this study used nominal concentrations, and therefore was not considered acceptable. In another study involving diesel fuel, the effect on brown or common shrimp (Crangon crangon) a 96-hour LC50 of 22 mg/L was determined. A "gas oil"was also tested and a 96-hour LC50 of 12 mg/L.was determined The steady state cell density of marine phytoplankton decreased with increasing concentrations of diesel fuel, with different sensitivities between species . The diatom Phaeodactylum tricornutum showed a 20% decrease in cell density in 24 hours following a 3 mg/L exposure with a 24-hour no-observed effect concentration (NOEC) of 2.5 mg/L. The microalga lsochrysis galbana was more tolerant to diesel fuel, with a 24-hour lovest-observed-effect concentration (LOEC) of 26 mg/L (14% decrease in cell density), and a NOEC of 25 mg/L. Finally, the green algae Chlorella salina was relatively insensitive to diesel fuel contamination, with a 24-hour LOEC of 170 mg/L (27% decrease in cell density), and a NOEC of 160 mg/L . All populations of phytoplankton returned to a steady state within 5 days of exposure

In sandy soils, earthworm (Eisenia fetida) mortality only occurred at diesel fuel concentrations greater than 10 000 mg/kg, which was also the concentration at which sub-lethal weight loss was recorded

Nephrotoxic effects of diesel fuel have been documented in several animal and human studies. Some species of birds (mallard ducks in particular) are generally resistant to the toxic effects of petrochemical ingestion, and large amounts of petrochemicals are needed in order to cause direct mortality

For n-Decane:

Koc: 22200 - 42700; log Kow: 5.98; Half-life (hr) air: 33.6; Half-life (hr) H2O Surface Water: 84 - 3120; Henry's atm m3/mol: 5.15; Log BCF: 3.52-4.31

Atmospheric Fate: n-Decane is expected to be readily degraded by reaction with photochemically produced hydroxyl radicals; photolysis is not expected to be an important fate mechanism. n-Decane is expected to have a half-life between 1 and 10 days in the atmosphere.

Terrestrial Fate: This chemical may biodegrade to a moderate extent is not expected to leach into groundwater and is expected to rapidly evaporate.

Aquatic Fate: n-Decane may biodegrade to a moderate extent and is expected to quickly evaporate. This material may bioaccumulate to some extent.

Ecotoxicity: n-Decane is moderately toxic to fish. **DO NOT** discharge into sewer or waterways.

Persistence and degradability

| Ingredient | Persistence: Water/Soil | Persistence: Air |
|--------------------|-------------------------|------------------|
| alkanes C3-4. | LOW | LOW |
| piperonyl butoxide | HIGH | HIGH |
| pyrethrin I | HIGH | HIGH |

Bioaccumulative potential

| Ingredient | Bioaccumulation |
|--------------------|----------------------|
| alkanes C3-4. | LOW (LogKOW = 2.89) |
| piperonyl butoxide | HIGH (LogKOW = 4.75) |
| pyrethrin I | HIGH (LogKOW = 5.9) |

Mobility in soil

| Ingredient | Mobility |
|--------------------|-------------------|
| alkanes C3-4. | LOW (KOC = 43.79) |
| piperonyl butoxide | LOW (KOC = 69.74) |
| pyrethrin I | LOW (KOC = 10460) |

SECTION 13 Disposal considerations

| Product / Packaging disposal | DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority. Consult State Land Waste Management Authority for disposal. Discharge contents of damaged aerosol cans at an approved site. Allow small quantities to evaporate. DO NOT incinerate or puncture aerosol cans. Bury residues and emptied aerosol cans at an approved site. |
|------------------------------|---|

SECTION 14 Transport information

Labels Required

| Marine Pollutant | |
|------------------|----------------|
| HAZCHEM | Not Applicable |

Land transport (ADG)

| UN number or ID number | 1950 | | |
|------------------------------|--|--|--|
| UN proper shipping name | AEROSOLS | | |
| Transport hazard class(es) | Class2.1Subsidiary riskNot Applicable | | |
| Packing group | Not Applicable | | |
| Environmental hazard | Environmentally hazardous | | |
| Special precautions for user | Special provisions63 190 277 327 344 381Limited quantity1000ml | | |

Air transport (ICAO-IATA / DGR)

| UN number | 1950 | | | |
|------------------------------|---|------------------------------|----------------|--|
| UN proper shipping name | Aerosols, flammable | Aerosols, flammable | | |
| Transport hazard class(es) | ICAO/IATA Class ICAO / IATA Subrisk ERG Code | 2.1 Not Applicable 10L | | |
| Packing group | Not Applicable | Not Applicable | | |
| Environmental hazard | Environmentally hazardous | | | |
| | Special provisions | | A145 A167 A802 | |
| | Cargo Only Packing In | nstructions | 203 | |
| | Cargo Only Maximum | Qty / Pack | 150 kg | |
| Special precautions for user | Passenger and Cargo | Packing Instructions | 203 | |
| | Passenger and Cargo Maximum Qty / Pack | | 75 kg | |
| | Passenger and Cargo Limited Quantity Packing Instructions | | Y203 | |
| | Passenger and Cargo Limited Maximum Qty / Pack | | 30 kg G | |

Sea transport (IMDG-Code / GGVSee)

| UN number | 1950 | | |
|------------------------------|----------------------------------|--|--|
| UN proper shipping name | AEROSOLS | | |
| Transport hazard class(es) | IMDG Class IMDG Subrisk | 2.1 Not Applicable | |
| Packing group | Not Applicable | | |
| Environmental hazard | Marine Pollutant | | |
| Special precautions for user | EMS Number Special provisions | F-D, S-U 63 190 277 327 344 381 959 | |

Continued...

Limited Quantities 1000 ml

Transport in bulk according to Annex II of MARPOL and the IBC code Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

| Product name | Group |
|--------------------|---------------|
| alkanes C3-4. | Not Available |
| C10-14 alkanes | Not Available |
| piperonyl butoxide | Not Available |
| pyrethrin I | Not Available |

Transport in bulk in accordance with the IGC Code

| Product name | Ship Type |
|--------------------|---------------|
| alkanes C3-4. | Not Available |
| C10-14 alkanes | Not Available |
| piperonyl butoxide | Not Available |
| pyrethrin I | Not Available |

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

| alkanes C3-4. is found on the following regulatory lists | |
|--|---|
| Australian Inventory of Industrial Chemicals (AIIC) | Chemical Footprint Project - Chemicals of H |

C10-14 alkanes is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

piperonyl butoxide is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

High Concern List

Australian Inventory of Industrial Chemicals (AIIC)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

pyrethrin I is found on the following regulatory lists

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -Schedule 2

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -Schedule 5

National Inventory Status

| National Inventory | Status |
|--|---|
| Australia - AIIC / Australia Non-Industrial Use | Yes |
| Canada - DSL | No (C10-14 alkanes) |
| Canada - NDSL | No (alkanes C3-4.; piperonyl butoxide; pyrethrin I) |
| China - IECSC | No (pyrethrin I) |
| Europe - EINEC / ELINCS / NLP | Yes |
| Japan - ENCS | No (pyrethrin I) |
| Korea - KECI | No (pyrethrin I) |
| New Zealand - NZIoC | Yes |
| Philippines - PICCS | No (C10-14 alkanes) |
| USA - TSCA | No (pyrethrin I) |
| Taiwan - TCSI | No (pyrethrin I) |
| Mexico - INSQ | No (C10-14 alkanes; pyrethrin I) |
| Vietnam - NCI | Yes |
| Russia - FBEPH | No (C10-14 alkanes; pyrethrin I) |
| Legend: | Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration. |

SECTION 16 Other information

| Revision Date | 04/04/2023 |
|---------------|------------|
| Initial Date | 04/04/2023 |

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit. IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index AIIC: Australian Inventory of Industrial Chemicals DSL: Domestic Substances List NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.